## ISUZU 5 tons isothermal van box truck

## Specification:

| ISUZU 5ton truck |   |   |
|------------------|---|---|
| General          |   | ISUZU   |
|                  | Overall<br>Dimension  | 5995X2180X3230 mm                             |
|                  | GVW / Kerb<br>Weight  | 8,280kg / 3,200kg                             |
| Cab              | Cab Capacity  | 2 persons allowed                             |
|                  | Air Conditioner   | Heating/cooling air conditioner               |
| Engine           | Fuel Type   | Diesel  |
|                  | Engine Brand  | 4KH1CN6LB                                     |
|                  | Power   | 120 HP (88 KW)                                |
|                  | Displacement  | 2999 ml                                       |
|                  | Emission<br>Standard  | Euro VI                                       |
| Chassis          | Drive Type  | 4X2 (left hand drive)                         |
|                  | Transmission  | ISUZU MSB 5-shift speed levers with 1 reverse |
|                  | Wheelbase/No.<br>of axle  | 3360 mm / 2                                   |
|                  | Tire<br>Specification   | 7.00R16                                       |
|                  | Tire Number   | 6 tires and 1 spare tire                      |
|                  | Max Speed   | 105 km/h                                      |
|                  | Paint   | Metallic paint                                |
| Superstructure   | Body size   | 4100×2000×2100(mm)                            |
|                  | Load Capacity   | 5 Tons  |
|                  | Panel Structure   | Fiber glass sandwich polyurethane             |
|                  | Front/Side/Rear<br>panel  | Panel Thickness: 85mm                         |
|                  | Roof/Floor<br>panel   | Panel Thickness: 105mm                        |
|                  | Lights & Switch   | Led, Water-proof, 12V/24V convertible         |
| Equipment        | FRP inside and outside the box, 8cm high-density thermal insulation board, the bottom plate is anti-slip patterned aluminum plate, and the rear door lock is stainless steel. |   |